

DATA CENTER SWITCH

AS9736-64D



The Edgecore DCS520 is a spine switch for high-performance data centers. The switch provides line-rate L2 and L3 switching across the 64 x QSFP56-DD ports, each supporting 1 x 400G QSFP56-DD, 1 x 100G QSFP28, 1 x 40G QSFP+, or via breakout cables 2 x 200G (2 x 4 lanes 50G PAM4), 4 x 100G (4 x 2 lanes 50G PAM4), 2 x 50G (2 x 2 lanes 25G NRZ), 4 x 25G NRZ, or 4 x 10G NRZ. The DCS520 can be deployed as a spine switch supporting 100/400 GbE spine to spine or spine to leaf interconnects. This open network switch is loaded with the Open Network Install Environment (ONIE), which supports the installation of compatible Network Operating System software, including the open source options Open Network Linux, plus commercial NOS offerings.

Key Features and Benefits

- QSFP56-DD switch ports, each supporting 1 x 400G QSFP56-DD, 1 x 100G QSFP28, 1 x 40G QSFP+, or via breakout cables 2 x 200G (2 x 4 lanes 50G PAM4), 4 x 100G (4 x 2 lanes 50G PAM4), 2 x 50G (2 x 2 lanes 25G NRZ), 4 x 25G NRZ, or 4 x 10G NRZ.
- Incorporates Broadcom Tomahawk 4 switch series silicon.
- 2 RU form factor.
- Supports hot/cold aisles with front-to-back airflow SKU.
- All ports on front; PSUs and fans accessible from rear.
- Hot-swappable, load-sharing, redundant 2400 W AC/HVDC PSUs.
- 3+1 redundant, hot-swappable fan modules.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible open source and commercial NOS offerings.
- Compatible with Open Network Linux (ONL), the open-source, OCP reference NOS.



Freedom
of choice



Greater
control




Rapid
innovation

Free Software Included



Interfaces



Description	
1. System LEDs	7. USB storage port
2. 16 x 400G QSFP56-DD ports (24 W) Support 400G QSFP56-DD DAC up to 2.5 m	8. PSU 1
3. 48 x 400G QSFP56-DD ports (13 W) Support 400G QSFP56-DD DAC up to 1 m	9. Hot-swappable 3 + 1 redundant fans
4. Console port	10. PSU 2
5. RJ-45 management port	11. Grounding point
6. 2 x 10G SFP+ management ports	

Ports

- Switch Ports: 64 x QSFP56-DD 400 GbE
Port Modes:
 - 1 x 400G (8 lanes 50G PAM4)
 - 2 x 200G (4 lanes 50G PAM4) QSFP56-DD breakout
 - 4 x 100G (2 lanes 50G PAM4) QSFP56-DD breakout
 - 1 x 100G (4 lanes 25G NRZ) QSFP28
 - 1 x 40G (4 lanes 10G NRZ) QSFP+
 - 2 x 50G (2 lanes 25G NRZ) QSFP28 breakout
 - 4 x 25G (1 lane 25G NRZ) QSFP56-DD breakout
 - 4 x 10G (1 lane 10G NRZ) QSFP56-DD breakout
- Management Ports on Port Side:
 - 1 x RJ-45 serial console
 - 1 x RJ-45 1000BASE-T management
 - 2 x SFP+ 10G management
 - 1 x USB 2.0 storage port
- Supported Transceivers and Cables:
 - 100GBASE-SR4/CWDM4/LR4
 - 100G-DAC/AOC Cable
 - 400BASE-FR4
 - 400G-DAC/AOC Cable
 - Note: More optics and detailed cabling information can be found at www.edge-core.com.

Key Components

- Switch Silicon: BCM56990 Tomahawk 4
- CPU Modules:
 - Intel® Xeon® Processor D-1548 8-Core 2.0 GHz
 - DDR4: 16 GB x 2 SO-DIMM
 - m.2 SSD: 128GB x 1

Performance

- Switching Capability: 25.6 Tbps full duplex
- Forwarding Rate: 10.42 Bpps
- Jumbo frames support up to 9416 bytes
- Packet Buffer Size: Integrated 113.66 MB packet buffer
- Subject to NOS:
 - MAC Addresses: 8K for exact match
 - 128K without exact match

Physical and Environmental

- Dimensions (WxDxH): 44 x 64.92 x 87 cm (17.32 x 25.56 x 34.25 in)
- Weight: 21.5 kg (47.4 lb), with 2 PSUs and 4 fans installed
- Fans: Hot-swappable 3 + 1 redundant fans
- Storage Temperature: -40°C to 70°C (-40°F to 158°F)
- Operating Temperature:
 - (FtoB): 0°C~40°C (32°F~104°F)
 - 0~40°C (32°F~104°F) at sea level,
 - 0~35°C (32°F~95°F) at 1828 m (6000 ft)
- Operating Humidity: 5% ~ 95% non-condensing
- Operating Altitude: 0-1828 m (0-6000 ft)

Software

- Switch is loaded with Open Network Install Environment (ONIE) software installer
- Compatible with the following NOS options:
 - Open Network Linux (ONL), the open-source, OCP reference NOS, Enterprise SONiC by Edgework

System and Port LEDs

- QSFP56-DD Port LEDs:
 - 400G (1 x 8 lanes 50G PAM4): Blue
 - 200G (2 x 4 lanes 50G PAM4): Cyan
 - 100G (4 x 2 lanes 50G PAM4): Green
 - 100G (1 x 4 lanes 25G NRZ): Green
 - 40G (1 x 4 lanes 10G NRZ): Dark Green
 - 50G (2 x 2 lanes 25G NRZ): Red
 - 25G (4 x 1 lane 25G NRZ): Orange
 - 10G (4 x 1 lane 10G NRZ): Yellow
- Management Port LEDs:
 - SFP+: Left: Green (10G link), Amber (1G link)
 - Right: Green (10G activity), Amber (1G activity)
 - RJ-45: Left: Green (1G link), Amber (10/100M link)
 - Right: Green (1G activity), Amber (10/100M activity)
- System LEDs: PSU1, PSU2, FAN, STAT, and LOC
- Reset button

Power

- PSUs: 2 redundant, load-sharing, hot-swappable 2400 W AC/HVDC power supplies
- AC PSU
Input Power Rating:
 - 100–127 VAC, 50/60 Hz, 12 A maximum
 - 200–240 VAC, 50/60 Hz, 15 A maximum
 - HVDC: 240 VDC, 15 A maximum
- Power Draw: 287.75 W (min.), 2100 W (max.)
- Power Budget:
 - Ports 1, 2, 3, 4, 29, 30, 31, 32, 33, 34, 35, 36, 61, 62, 63, 64: 24 W per transceiver
 - All other ports: 13 W per transceiver

Regulatory

- Emissions:
 - EN 55032 Class A
 - EN 61000-3-2
 - EN 61000-3-3
 - VCCI-CISPR 32 Class A
 - AS/NZS CISPR 32 Class A
 - ICES-003 Issue 7 Class A
 - FCC Class A
- Immunity:
 - EN 55035
 - IEC 61000-4-2/3/4/5/6/8/11
- Safety:
 - UL (CSA 22.2 No 62368-1 ☉ UL62368-1)
 - CB (IEC/EN60950-1 ☉ IEC/EN 62368-1)
- Environmental:
 - GR63-CORE (Pre-test)
- RoHS-2.0 Compliant
- Electrical and Electronic Equipment (WEEE Directive 2002/96/EC)

Ordering Information

Base Model: AS9736-64D; Intel® Xeon® D-1548 Processor 8-Core; 64-Port 400G QSFP56-DD; ONIE Software Installer.

Model Number	Part Number	PSU	Airflow	Power Cord
AS9736-64D-O-AC-F	FP5ZZ8664004A	Dual AC PSUs	Front-to-Back airflow	HVAC to IEC 60320 C20 (1m)

Warranty

Please check www.edge-core.com for the warranty terms in your country.

For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit www.edge-core.com.

About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2023 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.